

SAFETY DATA SHEET

in accordance with Commission Regulation (EU) No. 1907/2006

Page: 1

Compilation date: 03.09.2010

Revision date: 30.06.2015

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: KLEEN PRO PICCOMAT FS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Floor cleaner for machine application for professional users

1.3. Details of the supplier of the safety data sheet

Company name: KLEEN PURGATIS GmbH

Dieselstraße 10

D - 32120 Hiddenhausen

Deutschland

Tel: +49 (0)5223 - 9970-40

Fax: +49 (0)5223 - 9970-50

Email: info@kleen-purgatis.de

1.4. Emergency telephone number

Emergency tel: +49 (0)551 - 19240 (GIZ-Nord)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Classification under CHIP: C: R35

Most important adverse effects: Causes severe skin burns and eye damage.

*2.2. Label elements

Label elements under CLP:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Hazard components for labelling: Sodium hydroxide, Potassium hydroxide

Precautionary statements: P280: Wear protective gloves/eye protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 2

P309+311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor.

P405: Store locked up.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYDROXIDE - REACH registered number(s): 01-2119457892-27-0000

EINECS	CAS	CLP Classification	Percent
215-185-5	1310-73-2	Skin Corr. 1A: H314	10-20%

POTASSIUM HYDROXIDE - REACH registered number(s): 01-2119487136-33-0000

215-181-3	1310-58-3	Acute Tox. 4: H302; Skin Corr. 1A: H314	1-5%
-----------	-----------	---	------

HEDP - REACH registered number(s): 01-2119510391-53-0003

220-552-8	2809-21-4	Met. Corr. 1: H290; Eye Dam. 1: H318	1-5%
-----------	-----------	--------------------------------------	------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Let water be drunken in little sips (dilution effect). Medical treatment necessary.

Inhalation: Move affected person into fresh air. In case of respiratory tract irritation, consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 3

5.1. Extinguishing media

Extinguishing media: Water spray. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Keep unprotected people away and stay on the upwind side.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep away from food, drink and animal feedingstuffs. Storage class: 8B (Non-combustible corrosive substances)

Suitable packaging: Must only be kept in original packaging. Do not use aluminium containers.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 4

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m ³	-	-

POTASSIUM HYDROXIDE

UK	-	2 mg/m ³	-	-
----	---	---------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: not necessary.

Hand protection: Protective gloves. Suitable material: NR (natural rubber), CR (polychloroprene) or NBR (nitrile rubber), category III according to EN 374. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Breakthrough time (maximal wear duration): Wear duration with occasional contact, splashes (Level 2: < 30 min): Disposable-gloves, Thickness of the material 0,1mm. Wear duration with permanent contact (Level 6: < 480min): Protective gloves, Thickness of the glove material 0,7 mm. Breakthrough times and swelling properties of the material must be taken into consideration.

Eye protection: Tightly fitting safety goggles.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: product specific

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Non-viscous

Relative density: * 1,24 g/cm³

pH: >13

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Acids. Base metals.

10.6. Hazardous decomposition products

Haz. decomp. products: Release of Hydrogen (H₂)

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
Sodium hydroxide: ORL	RAT	LD50	2000	mg/kg
HEDP: ORL	RAT	LD50	2400	mg/kg

Symptoms / routes of exposure

Skin contact: Blistering may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
HEDP: Daphnia magna	48H EC50	527	mg/l
Oncorhynchus mykiss	96H LC50	368	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: no data available.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 6

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: The product has not been tested. Data apply to the components with the highest toxicological risk.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 20 01 29

Disposal of packaging: May be reused following decontamination.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1824

14.2. UN proper shipping name

Shipping name: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT FS

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Data references: Safety data sheets from our raw material suppliers

Department issuing MSDS: Product Development Department;

Contact: Ms. Tiemann, Ms. Klumpe

Classification for mixtures and used evaluation method

according to article 9 of regulation (EC) 1272/2008 [CLP]:

Calculation methode

Phrases used in s.2 and 3: H290: May be corrosive to metals.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.